



PHONE: 862-210-8906
Spectrum Collection

FAX: 973-521-7004

Order Department Open:
 8:00am to 5:30pm M-Th
 8:00am to 5:00pm F

CARPET - LVT - SHEET VINYL

12 COMMERCE ROAD FAIRFIELD, NJ 07004

WWW.GARDNERINDUSTRIES.COM

	<u>DEALMAKER & VIKING</u>	<u>WORKHORSE</u>	<u>PLAYER & HIGH ROLLER</u>	<u>DIPLOMAT</u>	<u>CITY HALL</u>
Construction	Multi-Level Pattern Loop	Level Loop	Multi-Level Pattern Loop	Textured Loop	Graphic Loop
Fiber	100% Recycalon Nylon	100% Recycalon Nylon	100% Recycalon Nylon	100% Recycalon Nylon	100% Recycalon Nylon
Dye Method	Solution Dyed	Solution Dyed	Solution Dyed	Solution Dyed	Solution Dyed
Tufted Weight	14 oz	20 oz.	15 oz	20 oz	24 oz
Gauge	1/10	1/10	1/10	5/1	1/10
Stitches Per Inch	8.8	8.5	7.5	9	7.5
Finished Pile Thickness	.087"	.124"	0.132"	.106"	.135"
Total Thickness	.249"	52 oz./sq yd	0.271"	.273"	.297"
Average Density	5793	5806	4091	6792	6400
Product Size	24" x 24" Tile	12 Ft. Wide	24" x 24" Tile	12 Ft. Wide	12 Ft. Wide
Packaging	8.88 sq yds/ctn	12 Ft. Wide	5.33/sq yds/ctn	12 Ft. Wide	12 Ft. Wide
Pattern Repeat	N/A	N/A	N/A	20/32" W x 1-10/32" L	19/32" W x 1-2/32" L
Primary Backing	Synthetic	Synthetic	Synthetic	Synthetic	Synthetic
Secondary Backing	SpectruLoc Tile	Actionbac	SpectruLoc Tile	Actionbac	Actionbac
Protective Treatments	Lifetime Stain Protection	Lifetime Stain Protection	Lifetime Stain Protection	Lifetime Stain Protection	Lifetime Stain Protection
Testing Results	Class 1 (ASTM E-648)	Class 1 (ASTM E-648)	Class 1 (ASTM E-648)	Class 1 (ASTM E-648)	Class 1 (ASTM E-648)
	<450 (ASTM E-622)	<450 (ASTM E-622)	<450 (ASTM E-622)	<450 (ASTM E-622)	<450 (ASTM E-622)
	< 3.5 kv (AATCC-134)	< 3.5 kv (AATCC-134)	< 3.5 kv (AATCC-134)	< 3.5 kv (AATCC-134)	< 3.5 kv (AATCC-134)
	Passes (AATCC-174)	Passes (AATCC-174)	Passes (AATCC-174)	Passes (AATCC-174)	Passes (AATCC-174)
Recommended Adhesive	SPECTRUM SA5000	AAT-Anchorbond	SPECTRUM SA5000	AAT-Anchorbond	AAT-Anchorbond
Environmental Certification	Green Label Plus Certification # GLP2671	N/A	Green Label Plus Certification # NSF 140	Green Label Plus Certification #NSF 140 Gold - GLP8472	Green Label Plus Certification #NSF 140 Gold - GLP8472
Warranty	10 Year Commercial Lifetime Stain	10 Year Commercial Lifetime Stain	10 Year Commercial Lifetime Stain	10 Year Commercial Lifetime Stain	10 Year Commercial Lifetime Stain

CARPET TILE INSTALLATION METHODS



Monolithic



Quarter Turn



Ashlar



Brick



Random



Chair pads are recommended.

Walk off mats are recommended at building entrances. Ask us for available options.

Colors may vary from dye lot to dye lot. As carpet is a textile material, a perfect pattern match is not guaranteed. Please refer to CRI recommended installation guidelines and techniques for a suitable match.