



12 Commerce Road Fairfield, NJ 07004

PHONE: 973-887-3700

Spectrum
Collection

FAX: 973-887-8052

Order Department Open:
8:00am to 5:30pm M-Th
8:00am to 5:00pm F

WWW.GARDNERINDUSTRIES.COM

LIKE us on FACEBOOK www.facebook.com/GardnerIndustriesInc

SPECTRUM RIGID CORE Price List

RIGID CORE PLUS

RIGID CORE CLASSIC

RIGID CORE HOME

RCP-61011-1 JERSEY OAK	RCC-41011-1 JERSEY OAK	RCH-1007 UPTOWN GREY
RCP-61012-3 DRIFTWOOD	RCC-41012-3 DRIFTWOOD	RCH-16398 SHADOW GREY
RCP-61022-8 METRO GREY	RCC-41022-8 METRO GREY	RCH-1035 FROST GREY
RCP-61024-6 NEWPORT GREY	RCC-41024-6 NEWPORT GREY	RCH-1407 BARNSIDE
RCP-61028-4 ACACIA NATURAL	RCC-41028-4 ACACIA NATURAL	RCH-1012 TIMBERLAND
RCP-6191-09 VINTAGE OAK	RCC-4191-09 VINTAGE OAK	
RCP-6206-4 AMERICAN HICKORY	RCC-4206-4 AMERICAN HICKORY	
RCP-66112-4 ACACIA DARK	RCC-46112-4 ACACIA DARK	
RCP-68050-2 SILVER FOX	RCC-48050-2 SILVER FOX	
RCP-69191-4 SOHO GREY	RCC-49191-4 SOHO GREY	
RCP-69641-01 NATURAL HICKORY	RCC-49641-01 NATURAL HICKORY	

MOLDING/TRIMS AVAILABLE IN MATCHING COLORS - CONTACT US

PRODUCT SPECS:	6.0mm (4.5mm+1.5mm IXPE pad)	5.0mm (4.0mm+1.0mm IXPE pad)	4.5mm (3.5mm+1.0mm IXPE pad)
WEARLAYER:	.55 mm (22 mils) wearlayer with ULTIMATE Ceramic Bead UV coating	.30 mm (12 mils) wearlayer with ULTIMATE Ceramic Bead UV coating	.30 mm (12 mils) wearlayer with Ceramic Bead UV coating
EMBOSSING:	Semi-EIR Registered Embossed	Semi-EIR Registered Embossed	Semi-EIR Registered Embossed
PLANK SIZE:	7" wide X 48" long	7" wide X 48" long	7" wide X 48" long
SQ FT/CTN	18.75 sq ft/ctn	23.50 sq ft/ctn	28.60 sq ft/ctn
CTNS/PALLET	60 ctns/pallet	54 ctns/pallet	55 ctns/pallet
WARRANTY:	<u>LIFETIME Waterproof</u>	<u>LIFETIME Waterproof</u>	<u>LIFETIME Waterproof</u>
	<u>LIFETIME Residential</u>	<u>30 Year Residential</u>	<u>25 Year Residential</u>
	<u>30 Year Commercial</u>	<u>10 Year Commercial</u>	<u>10 Year Lt Commercial</u>
	<u>Kid & Pet Proof</u>	<u>Kid & Pet Proof</u>	<u>Kid & Pet Proof</u>
	<u>Scratch Resist</u>	<u>Scratch Resist</u>	<u>Scratch Resist</u>
	<u>FLOOR SCORE® CERTIFIED</u>	<u>FLOOR SCORE® CERTIFIED</u>	<u>FLOOR SCORE® CERTIFIED</u>

TESTING: Chemical Resistance ASTM F925 - Superior - no change during testing
 Color Resistance to Heat -ASTM F1514 - Meets <8.0 Delta E Requirement
 Critical Radiant Flux ASTM E648 - Class I
 Emissions Testing CAL 1350 - meets requirements
 IIC Sound Rating - 64
 Measuring Heat Stability ASTM F1514 - Passes
 Static Coefficient of Friction ASTM 2047 - Passes
 Static Load Limit ASTM F970 - .002 inch- Passed at 250 psi
 Surface Flammability DOC FF 1-70 - Passes
Taber Abrasion ASTM D4060 - up to 18,000 cycles

INSTALLATION: On, above or below grade (for indoor use only)



Refer To Terms and Conditions of Sale
 Prices Subject To Change Without Notice.

Effective January 1, 2020

spectrumrcb-noprices